

Buffer Issue Resolution Document (BIRD)
BIRD ID#: {TBD}
ISSUE TITLE: AMI Function Return Value Clarification
REQUESTOR: Arpad Muranyi, Mentor Graphics
DATE SUBMITTED:
DATE REVISED: May 16, 2011
DATE ACCEPTED BY IBIS OPEN FORUM:

STATEMENT OF THE ISSUE:

The IBIS 5.0 specification defines the return values of the AMI_Init and AMI_GetWave functions as "1" for success and "0" for failure, but doesn't define what constitutes success or failure. As a result, some models return a failure code (0) when even if they only have functional problems but are still able to complete execution successfully, while other models return a failure code (0) when they crash due to program execution failures. Not knowing the nature of the error code, it is difficult to implement the proper exception handling in the EDA tools.

STATEMENT OF THE RESOLVED SPECIFICATIONS:

On pg. 188 and 189 insert after these lines:

| 1 for success
| 0 for failure

the following lines:

| Algorithmic models shall return a failure code (0) if and only if the
| function call fails due to a program execution error. In all other
| cases the return code shall be "success" (1), even if the function
| cannot operate properly due to some functional problems. For example,
| if a function includes a CDR which is unable to get into a stable mode,
| the function shall still return a success code (1). Examples for
| returning a failure code (0) may include an invalid data type, a
| null pointer during run time, or anything that prevents the successful
| execution of the model's code.
|

ANALYSIS PATH/DATA THAT LED TO SPECIFICATION:

There is an (unspoken) agreement between software developers that the function returns a failure code when the function call fails, but not when the device it models cannot operate properly.

ANY OTHER BACKGROUND INFORMATION:
