	A	В	
1	IBISv5.0 AMI specification BIRD task list		
		Clarification	
S	Description	or	New f
2 3		correction	
	Parser developer questions (and some more related ones)		
	first token - is it required to be the file name? no, the first token in the file actually does not need to be checked for matching to the filename; while this may be added as	5.1	
5	a restriction later, this is a LISP-ism and so may actually be any string.		
	- is it required or optional ("The file must have 2 distinct sections, or sub-trees")? (provided to parser developer by Arpad) Per our discussion today in the ATM meeting and Ambrish's approval, please tell the parser developer, that the intent was to have an optional Model Specific section in the .ami file which	5.1	
6	means that there is no requirement to have 2 sections at all times in the .ami file. We will write a BIRD to make the necessary changes in the specification.		
0	case sensitivity	5.1	
7	- are .AMI files case sensitive? yes	J. I	
	line length limit - is there a line length limit in .AMI files? Only the Description string in the .AMI file was intended to have a 120 character limit *per line* (the Description string	5.1	
8	can span multiple lines). The rest of the AMI file lines are effectively unlimited in length.	0.1	
	comment character		
	- define comment character for .AMI files in the AMI portion of the spec. - what is the comment character in .AMI files? For .AMI files only the character is acceptable as a comment character, regardless of what the calling IBIS	5.1	
	file uses.	0.1	
9	- why is "//" used in an example? That example is a C source code excerpt from the DLL		
	white space - define what it is in .AMI files spaces and tabs, including new lines		
	in .AMI file anything is allowed	5.1	
	No attempt needs to be made to be consistent with .IBS files.		
	string - define what it is	5.1	
	integer	5.1	
	- define what it is float	0.1	
	- define what it is	5.1	
	scale factors	5.1	
	<ul> <li>clarify no .AMI files do not permit scaling factors or suffixes such as p, n, etc. Scientific and floating point notation is permitted.</li> <li>Fix examples with string parameters to match the string definition.</li> </ul>	5.1	
	min/typ/max		
	- define possible values		
	- is increment always positive? yes - does default have to obey min <= default <= max? I would think yes	5.1	
	Default must be a legal value according to Format. Solved in the Typos BIRD (BIRD 127).		
16	Sweep starts at typ, tool goes up closest to max, then goes down closest to min.		
	Increment is therefore always a positive number. Init_Returns_Impulse and GetWave_Exists True		
	- inconsistent (correct)		
	- is the parameter "Default" not allowed for it? (provided to parser developer by Walter) There is no default for these two; they must be specified. The BIRD		
	should be amended to say something like:		
	and are required if the [Algorithmic Model] keyword is		
	present. The entries following the reserved parameters		
	points to its usage, type and value. All reserved parameters must be in the following format:		
	(parameter_name (Usage <usage>) (Type <data_type>)</data_type></usage>		
	(Value <values>) (Description <string>))</string></values>	5.1	
	further down:		
	Reserved Parameter Required Value Info In Out InOut		
	   Init Returns Impulse Yes True/False X		
	GetWave Exists Yes True/False X		
	Technically Init is always used, and is required to be called before CotMays. The sympthty as medified impulse responses of Init may as may not be associated.		
	Technically Init is always used, and is required to be called before GetWave. The output, or modified impulse response of Init may or may not be generated. If not generated, then it is academic to say that the EDA tool can "use" it.		
	Arpad: This is all solved now, not exactly as suggested here, but based on the new discussions/suggestions. (BIRD 127 took care of this).		

2	D	E
eature	BIRD file name	Date done
	Definitions_BIRD.txt (BIRD 114)	August 24, 2010
	Typos_Format_Value_ Default_BIRD.txt (BIRD 127)	January 18, 2011
	Definitions_BIRD.txt (BIRD 114)	August 24, 2010
	Definitions_BIRD.txt (BIRD 114)	August 24, 2010
	Definitions_BIRD.txt (BIRD 114)	August 24, 2010
	Definitions_BIRD.txt (BIRD 114)	August 24, 2010
	Definitions_BIRD.txt (BIRD 114)	August 24, 2010
	Definitions_BIRD.txt (BIRD 114)	August 24, 2010
	Definitions_BIRD.txt (BIRD 114)	August 24, 2010
	Definitions_BIRD.txt (BIRD 114)	August 24, 2010
	BIRD 114	September 8, 2010
	MinTypMax_BIRD.txt	September 21, 2010
	Typos_Format_Value_ Default_BIRD.txt (BIRD 127)	January 18, 2011

Α В **IBISv5.0 AMI specification BIRD task list** Clarification New Description or 2 correction "Format", "Value", "Default" - define rules 1) For the first 5 Reserved Parameters (listed on p. 145 of the PDF and below), the following two rules are to be observed: "Format" is illegal and is therefore prohibited "Default" is required and must be present 2) For all other Reserved Parameters and model-specific parameters, "Format" is required and must be present "Default" is optional and may or may not be present 5.1 Recall that the first 5 Reserved Parameters covered by (1) above are: GetWave\_Exists, Init\_Returns\_Impulse, Use\_Init\_Output, Max\_Init\_Aggressors and Ignore\_Bits. This means that the text description on page 144 of the 5.0 specification is correct. Table 1 and Table 3 of Section 6c have certain ambiguities, as you have highlighted, which these two rules will correct. A future version of the specification will make this clearer and more explicit. Note that these two rules build in an ambiguity about the relationship between "Format" and text strings. We advise flagging a warning that these are not currently parsed or covered in the specification (your choice). 18 What is the amibuity, and does it need to be corrected??? (See row 25) Usage, Type, Format issues: Wording on pg. 140 of the specification may imply that: Usage is optional for Reserved Parameters Type and Format are optional since defaults are defined for them 5.1 Based on the stated and agreed upon syntax rules, Usage and Type are always required. No defaults are needed. Currently, Format always requires an argument starting with a word from the list: Value, Range, List, Corner, Increment, Steps, Table, Gaussian, Dual-Dirac, DjRj. No default exists for Format. However, Walter is working on a BIRD to make Format optional and eventually deprecate it. 19 Table - is a space required after "Table"? The "Table" format is specifically named as a "branch", which must have white space separating its name, "Table", from its value. pg 186: 2. Parameter name/value pairs are always enclosed in parentheses, with the value separated from the name by white space. 5.1 pg. 140: Table The parameter name "Table" names a branch of the parameter tree rather than a single leaf. One of the leaves of this branch can be named "Labels" and, if provided, is to be 20 assigned a string value containing a list of column names. According to the BNF, the Format = Table syntax is invalid. In this example: (Format Table (Labels Row\_No Time Probability) (-5 -5e-12 1e-10) (-4 -4e-12 3e-7) Instead of the Table keyword, a list is expected according to the spec. If the table syntax would be changed to the following, then it would be consistent with the spec .: 5.1 (Format (Table (Labels Row\_No Time Probability) (-5 -5e-12 1e-10) (-4 -4e-12 3e-7) ) BIRD 127 only fixed "Format". If Format is removed, this s not a problem, but if Format is there the problem still exists. We need to fix this. 21 The syntax for a leaf is: 5.1 <leaf>: ( <parameter name> whitespace <value list> ) 22 So in a Table which is written like this: (-50 -0.1 1e-35), -50 is actually a parameter name, i.e. a string, not a value. Need answer! Is NA in Table 1 correct for Default of Init Returns Impulse and GetWaveExists? (Why do we have default for a required parameter which implies that it is not required)? 5.1 - it is required, so why NA? Arpad: The table has to be corrected to reflect what is in the text.

С	D	E
	PIPD	
eature	BIRD file name	Date done
	Typos_Format_Value_ Default_BIRD.txt (BIRD 127)	January 18, 2011
	Typos_Format_Value_ Default_BIRD.txt (BIRD 127)	January 18, 2011
	False alarm. The spec doesn't say that a branch must be separated from its value by a white space.	Do nothing. Sepember 10, 2010
	Typos_Format_Value_ Default_BIRD.txt (BIRD 127)	January 18, 2011
	Table_Clarification_BIRD.txt (Ambrish)	
	Table1_3_BIRD.txt (Bob)	

	Α	В	С	D	E
1	IBISv5.0 AMI specification BIRD task list				
2	Description	Clarification or correction	New feature	BIRD file name	Date done
	Incorrect examples for: (Init_Returns_Impulse (Usage Info) (Type Boolean)(Default True)) (GetWave_Exists (Usage Info) (Type Boolean) (Default True)) according to Table 3, the Format must be specified and must be of format type "Value". - Note that some of the rules build in an ambiguity about the relationship between "Format" and text strings. Arpad: The examples are correct based on the rules in the text, the table has to be corrected to reflect what is in the text.	5.1		Typos_Format_Value_ Default_BIRD.txt (BIRD 127)	January 18, 2011
	Define relationship between Type and Format (allowable possible combinations)         For example,         if Type = Tap what are the allowable Formats ?         Is it OK to use Corner Format with String type ?         How is UI different from Float ?         According to Walter:         Type         Allowed Formats         Boolean       Value, List, Corner         String       Value, List, Corner, Range, Increment, Steps         Integer       Value, List, Corner, Range, Increment, Steps         UI       Value, List, Corner, Range, Increment, Steps         Tap       Value, List, Corner, Range, Increment, Steps         UI       subscriptically is used to describe the values of parameters that are in Seconds. If the Type is Float, then a value of 10e-12 would be interpreted at 10ps. If the Type is UI, and the bit_time was 100ps, then a value of .1 would be interpreted by the EDA tool (and the DLL) as 10ps. <td>5.1</td> <td></td> <td>Type_Format_Table_BIRD.txt (Ambrish)</td> <td></td>	5.1		Type_Format_Table_BIRD.txt (Ambrish)	
	What about Format Table, Gaussian, DjRj and Dual-Dirac? (See row 46-47)	row 46-47	row 46-47	row 46-47	row 46-47
	Description - define rules, required/optional about a year ago we agreed to a rule that Description is required for Reserved_Parameters and optional for Model_Specific - based on picking out actual parts of Section 6c that supported the above rule. The Parser enforces this rule. I think making Description optional is the best way to go and a compromise. Otherwise we change compliant models. Bob (It is now optional according to BIRD 127).	5.1		Typos_Format_Value_ Default_BIRD.txt (BIRD 127)	January 18, 2011
27					
29	AMI flow related				
30	Order of EDA tool convolution and first Tx GetWave call	5.1		AMI flow BIRD (BIRD 120)	October 5, 2010
	add parameter: Init_Returns_Filter		5.1+		
	process Rx pad waveform with Rx_GetWave impulse_matrix - can AMI_Init only modify the first column? - how about modifying the IR of cross talk aggressors? According to Walter: AMI_Init can only modify the first column AMI_Init may not modify the crosstalk (not first) columns - need to discuss in light of the flow	5.1	5.1+	Xtalk_BIRD.txt (BIRD 130)	April 12, 2011
	clock_times	5.1		clock_times_BIRD.txt	May 4, 2010
34	<ul> <li>- clarify various topics</li> <li>impulse response</li> <li>- define how it is generated</li> <li>- clarify what is its unit</li> <li>- what should be done in absence of an analog IBIS model?</li> <li>- if Thevenin (LTI) buffer is used, what should be the amplitude?</li> <li>- what tap coefficients should the analog model represent? Driver without EQ, already in spec</li> </ul>	5.1		(BIRD 112)	
	<ul> <li>parameter string (passed into the DLL)</li> <li>- are quotes and other special characters (tabs, CRLF, etc) allowed? answer ??? (BIRD 127 took care of this).</li> <li>A string is anything between two double quotes. Anything legal in IBIS except a double quote is allowed in that string.</li> <li>- clarify rules on how it is extracted from an .AMI file</li> <li>Leaving the Table aside, the rules in the BNF are quite clear. (According to Walter)</li> <li>- double quotes are not allowed except surrounding string variables</li> <li>- any ASCI character (except ") are allowed between " surrounding string variables</li> <li>- tabs, CRLF are treated as white space</li> <li>- BNF as described in BIRD 5.0 (Noting that (Reserved_Parameter and (Model_Specific branches are eliminated</li> <li>- each parameter is followed by one of the allowed values specified for that parameter.</li> </ul>	5.1		Typos_Format_Value_ Default_BIRD.txt (BIRD 127)	January 18, 2011

	Α	В	C
1	IBISv5.0 AMI specification BIRD task list		
<u>⊢</u>		Clarification	
	Description	or	New fea
2		correction	
	AMI parameters in / out		
	- describe what the purpose of parameters out is		
	The purpose of parameters out is for the AMI_Init call, and the AMI_GetWave calls to return to the EDA tool the values of Usage Out and InOut		
	parameters. The EDA tool is to either report these values to the user, or use these values as specified by IBIS if they are reserved parameters,	5.1	
	or by the model maker if they are Model Specific parameters. (According to Walter) BIRD 127 does NOT address all of the issues!!!		
	- which function (Init or GetWave) are allowed to return such values?		
37	- how would the EDA tool know how to deal with Model_Specific parameters?		
- 57	Usage related questions - clarify (Fangyi)	P	
	1. If a parameter is of Usage Info, shall it be included in the input parameter string to the Init call?		
	2. If a parameter is of Usage Out, shall it be included in the input parameter string to the Init call?		
	3. If a parameter is of Usage InOut, shall it be included in the input parameter string to the Init call?		
	4. If a parameter is of Usage Info or Out, can its sub-parameter be of Usage In?		
	Walter: According to pg. 140 "Clearly In and InOut are required to be in the input parameters string. Well-written EDA tool should not put Info and Out in the input		
	parameter string. Well-written DLL's should ignore Info and Out parameters in the input parameter string, or any other parameter that is not specified in the AMI file that		
	the EDA tool passes to it. Well-written DLLs should put all Out and InOut parameters in the output parameter string. Well-written EDA tools should ignore In and Info		
	parameter and other unknown parameters in the output parameter string. Well-written EDA tools should expect that all InOut and Out parameters are in the output		
	parameter string, but handle gracefully when these Out and InOut parameters are not returns in the output parameter string.		
			1
	Regarding question 4, your question is worded in a misleading way. "sub-parameter" is not defined in IBIS 5.0. I believe that the following explanation does represent the		
	intent of question 4.		
	The current specification is clear that various combinations of question 4 are problematic. Assuming that parameter can be In, InOut, Info, or Out, and its sub parameter	5.1	
	can independently be In, InOut, Info, or Out, there are 16 possible combinations, and some of them would violate the following rule.		
	1.2. Devene tex neme (velue neire exercise enclosed in nevertherees, with the		
	2. Parameter name/value pairs are always enclosed in parentheses, with the		
	value separated from the name by white space.		
	One problematic example:		
	(root		
	(Model_Specific		
	(Xyz (Usage In) (Type Integer) (Range 0 0 5) (Description "Xyz configuration")		
	(Abc (Usage In) (Type Integer) (Range 0 –10 10) ("Description Xyz Abc control"))		
38	The following input parameter string would violate the 2. rule above: (root (Xyz 3 (Abc -5)))		
			1
	Add: "It is only the leaves of a parameter tree that can have Usage defined for them" Need page number (BIRD 127 took care of this).	5.1	
39		Į/	l
	Change "parameter" to "AMI parameter" in:		1
	A leaf is a <b>parameter</b> if the leaf only contains sub-parameters.		1
	A lear is a <b>parameter</b> in the lear only contains sub-parameters.	5.1	1
	A parameter tree contains a root, branches and leaves. A branch of the parameter tree is	0.1	1
	an AMI Parameter, if it has one of the following leaves:		1
40	Where is this in the spec? Need a page number (BIRD 127 took care of this).		1
		E A	
41	Add a reserved parameter to the .ami file for version control	5.1	
42 43			
44	List from existing BIRD draft (as of February 23, 2010)		
	remove branches: Reserved_Parameters, Model_Specific		5.1-
	remove reserved parameters: Tx_Jitter, Rx_Clock_PDF (See BIRD 123)	???	<b> </b>
	remove keywords: Format, Gaussian, Table, DjRj, Dual-Dirac (See BIRD 123)	???	
48	add keyword: Array	Į/	5.1-
	New issues discovered		
50	AMI_parameters_out		
	- optional for AMI_GetWave only?		1
	- specify that if not returned the pointer should be a valid NULL pointer	5.1	1
51			1
		/	4

C	D	E
eature	BIRD file name	Date done
	Typos_Format_Value_ Default_BIRD.txt (BIRD 127) Out_InOut_BIRD.docx (Walter)	January 18, 2011
	Typos_Format_Value_ Default_BIRD.txt (BIRD 127)	January 18, 2011
	Typos_Format_Value_ Default_BIRD.txt (BIRD 127)	January 18, 2011
	Typos_Format_Value_ Default_BIRD.txt (BIRD 127)	January 18, 2011
	Version_BIRD.txt (BIRD 126)	December 14, 2010
	(120)	
1+		
1+		
	AMI_ParametersOut _BIRD.txt	

Α	В	С	D	E
1 IBISv5.0 AMI specification BIRD task list				
2 Description	Clarification or correction	New feature	BIRD file name	Date done
What should the tool do without clock times?				
- need to specify how the tool should sample the waveform		5.1+		
52 - address other SERDES protocols which use external clocking				
53 Labels BIRD draft from Walter?		5.1+		
Format Corner and Range interpretation				
- spell out what makes the selection for Corner and Range			AMI CornerRange	
- is it the tool's corner setting?	5.1		_BIRD.txt	
- if so, how does typ/min/max align with typ/slow/fast for Corner?				
54 - is it supposed to be shown in a GUI for the user to make a selection?				
55 Add Boolan to the BNF	5.1		AMI_BooleanInBNF _BIRD.txt	
56 What should be in the parameter string when there are no Model_Specific parameters at all?	5.1			
57 Should (Usage Out) parameters have Default or a Value at all?	5.1			
58 Existing Reserved_Parameters of (Usage Out) need definition for which function resturns them (Init or GetWave)		5.1+		
59 Model_Specific parameters should not be (Usage Out) or (Usage InOut)		5.1+		
60 Make sure Table 1 on pg. 148 doesn't show Ignore_Bits as Out	5.1		reminder for row 23	reminder for row 23
Clarify what kinds of failures should result in "0" in the function's return value (Section 3.1.3 and 3.3.3)			AMI FunctionReturnValue	
- function call failure	5.1		BIRD.txt	
61 - model cannot operate properly (CDR getting out of lock)			Birdbitkt	
62				
63				
Scott's suggestion:				
1) clarification				
- top level clarification BIRD -> full document, rewrite 5.0 with clarifications				
64 - subset -> clarification sub-BIRD-s to clarify specific things (clock_time, flow, etc)				
65 2) new stuff in separate BIRD-s (justification and proposed solutions)				
66				
Bob's suggestion:				
One BIRD that would be needed as a starting point is to correct/clarify Section 6c statements and examples according to these rules that were agreed upon for releasing	9			
67 the parser.				